



Patient Monitor AB-60

Patient Monitor AB-60 Plus



Features:-

- 12.1" color TFT display.
- Separated alarm and beep sound setting.
- Machine have separated boards for all parameters (AB-60 Plus Model)
- Real time ST Analysis and ARR analysis.
- 7-lead ECG waveforms display, built-in rechargeable battery with 4 hours battery backup.
- Multi-display: Standard, Large Font, Trend Coaxis, OxyCRG dynamic.

Standard Parameters:

5-lead ECG, SpO2, NIBP, Resp, Temp, PR

Optional:

Touchscreen, Printer, EtCO2, 2-IBP, 12-lead ECG, Masimo/Nellcor SpO2, Wall Mount, Trolley, SD card & USB Port, etc.



AB-60/ AB-60 Plus Patient Monitor

Technical Specifications

<p>ECG</p> <p>Input: 3/5 wires ECG cable Lead Section: I,II,III, aVR, aVL, aVF, V Gain Selection: x1/4, x1/2, 1x2x4 and automatic Sweep speed: 6.25, 12.5, 25, 50 mm/s Heart rate range: 15~300bpm Calibration:±1mv Accuracy:±bpm or ±1% (select the bigger data)</p>	<p>2-Temperature (Rectal & Surface)</p> <p>Number of channel: 2channel Measurement range: 25d'~45d' Accuracy: ±0.2d' Resolution: 0.1d' Display: T1, T2, T Unit: d/ selection</p>	<p>2-IBP /4-IBP (Option)</p> <p>Measurement range: 10~300mmHg Number of channel : 2 channel Accuracy: ±1mmHg or ±2% (select the bigger data) Pressure tag: ART, CVP, RVP, LAP, RAP, PAP, ICP, LVP</p>
<p>SP02</p> <p>Display type: Waveform, Data Measurement range: 0~100% Accuracy:±3% (between 70%~100%) SP02 resolution:1% Pulse rate range:30~250bpm Accuracy:±1bpm or ±2% (select the bigger data) PR Resolution: 1bpm</p>	<p>2-Respiration (Impedance & Nasal Tube)</p> <p>Measurement range: 0~120bpm Accuracy:±1bpm or ±5% (select the bigger data) Resolution: 1bpm</p>	<p>Cardiac Output (Option)</p> <p>Measurement Method : Themodilution Measurement & range: CO: 0.1~20.0L/min, TB:23.0d~43.0d TI:0.0d~27.0d Accuracy: C.O.: ±0.2L/min, TB±0.2d;TI:±0.2d Resolution : CO:0.1L/min; TB: 0.1d; TI: 0.1d</p>
<p>NIBP</p> <p>Philosophy: Oscillometric method Measurement type: SBP: (0~40)kPa; (0~300)mmHg; DBP: (1.3~26.7)kPa; (10~200)mmHg; MAP: (2.7~29.3) kPA; (20~220)mmHg; Resolution; 1mmHg Accuracy; Static: ±3mmHg Clinical: ±5mmHg standard deviation: 8mmHg Alarm tolerance: ±5%</p>	<p>ETC02 - Plug & Play (Option)</p> <p>Measurement type: main/side stream Measurement range: 0~19.7%; 0~150mmHg; 0~20kPa Accuracy: 0~40mmHg: ±2mmHg 41-70mmHg: ±5% 71-100mmHg: ±8% 101-150mmHg: ±10%</p>	<p>Anesthesia gas analysis (Option)</p> <p>Method: Infrared Absorption Gas Sorts: CO2, N2O, Des, Iso, Enf, Sev, Hal and optional O2 Measurement range: CO2 0~10%; N2O: 0~100% O2:5~100%; Hal: 0~8.5%, 150: 0~8.5% Enf: 0~10%; Sev: 0~10%; Des: 0~20% RR (Respiration rate): 0~100bpm Date: input Fi and Et values Agent mixture detection</p>

ACER BIOMEDICALS LLP

Office: Industrial Unit-80, Block-G, Sector-63, Noida, UP - 201301 (India)
Ph.: +91-120-4166921, **E-mail:** info@acerbiomed.com
Web.: www.acerbiomedicals.com, www.acerbiomed.com

Service Helpline
18008894232

