



## Features

- High accuracy Vital Signs monitor NIBP SpO2 PR TEMP
- 3.5inch screen for operation manual SpO2 PR pleth and TEMP
- 7 segment LEDS for Systolic pressure, Diastolic Pressure, MAP/CUFF pressure
- History Patient data review
- SpO2 Pitch & SpO2 workable in Neonate
- Capture dynamic waveforms
- Adjustable audible and visual Alarms
- Adjustable brightness
- Time delay switch-off function keep the monitor data restart monitor
- Complete and flexible mounting solution for transportation and in patient monitoring

### NIBP:

Method: Oscillometry  
Modes: Manual/Auto/Continuous  
Auto measure: time Adjustable  
Measurement range : 10-270mmHg

**Size:** L9.5 \* W6.5 \* H8.5 inch

**Weight:** 1.700 kg

### Pulse rate:

Range 20-254bpm  
Accuracy  $\pm 3$ bpm

### Electrical Specification:

100-240v AC, 50/60Hz

### Respiration:

Method RA-LL impedance  
Range

**Max Input Power:** 70VA

**Adult:** 0-120bpm

pediatric/neonatal:0-150bpm

Apnea alarm: Yes

### Battery:

11.1V 4000mAh rechargeable

lithium battery

### SPO2:

Measurement range: 0-100%  
Accuracy: 70-100%,  $\pm 2\%$  0-69%,  
unspecified

### Standard Configuration

SpO2, PR, NIBP



# VM-20

(8" Display)

(VITAL SIGN MONITOR  
SPO2 & NIBP)

## Features

8-Inch high-resolution color TFT/LCD display  
Lasting working capability with built-in rechargeable lithium battery  
400 groups of NIBP list, 60 alarm event record  
Central monitoring system applicable to ICU/CCU/OT  
Support solution: Wall mounting, mobile trolley



### NIBP:

Method: Oscillometry  
Modes: Manual/Auto/Continuous  
Auto measure: time Adjustable  
Measurement range : 10-270mmHg

**Size:** L9.5 \* W6.5 \* H8.5 inch

**Weight:** 1.700 kg

### Pulse rate:

Range 20-254bpm  
Accuracy  $\pm 3$ bpm

### Electrical Specification:

100-240v AC, 50/60Hz

### Respiration:

Method RA-LL impedance  
Range

**Max Input Power:** 70VA

**Adult:** 0-120bpm

pediatric/neonatal:0-150bpm  
Apnea alarm: Yes

### SPO2:

Measurement range: 0-100%  
Accuracy: 70-100%,  $\pm 2\%$  0-69%,  
unspecified

### Battery:

11.1V 4000mAh rechargeable  
lithium battery

### Standard Configuration

SpO2, PR, NIBP

## ACER BIOMEDICALS LLP

Office: Industrial unit -80, Block-G, Sector-63, Noida, U.P(India) 201301

+91 120 4166921, E-mail: [info@acerbiomed.com](mailto:info@acerbiomed.com)

Web: [www.acerbiomedicals.com](http://www.acerbiomedicals.com), [www.acerbiomed.com](http://www.acerbiomed.com)

Service Helpline

+91-120-4166921

